

PLUS

	V3-131	V-332	U4-232h	U4-237	U5-111	U5-112	U5-512	U5-732	U5-832	U7-132	U7-132h	U7-137
												
Resolution	XGA	XGA	XGA	XGA	SVGA	SVGA	SVGA	XGA	XGA	XGA	XGA	XGA
Brightness	1000 Lumens	1200 Lumens	2000 Lumens	2000 Lumens	1600 Lumens	1600 Lumens	1800 Lumens	2300 Lumens	2200 Lumens	3000 Lumens	3500 Lumens	3500 Lumens
Contrast Ratio	2000:1	2000:1	2000:1	2000:1	2000:1	2000:1	2000:1	2000:1	2000:1	2000:1	2000:1	2000:1
Weight	2.4 Lbs	2.8 Lbs.	3.3 Lbs	3.5 Lbs	4.1 Lbs	4.1 Lbs	4.2 Lbs	4.6 Lbs	4.4 Lbs	6.6 Lbs	6.6 Lbs	6.8 Lbs
Lens Type	Manual Focus	1:1.2 Manual Zoom	1:1.2 Manual Zoom	1:1.2 Manual Zoom	Short Focus Lens	1:1.2 Manual Zoom	1:1.2 Manual Zoom	1:1.2 Manual Zoom	1:1.2 Short Focus Zoom Lens	1:1.2 Manual Zoom	1:1.2 Manual Zoom	1:1.2 Manual Zoom
Lamp Life	1000-1500 Hrs.	1500 -2000 Hrs.	1500-2000 Hrs.	1500-2000 Hrs.	2000-3000 Hrs.	2000-3000 Hrs.	2000-3000 Hrs.	2000-3000 Hrs.	2000-3000 Hrs.	2000-3000 Hrs.	2000-3000 Hrs.	2000-3000 Hrs.
Aspect Ratio	4:3 support 16:9	4:3 support 16:9	4:3 support 16:9	4:3 support 16:9	4:3 support 16:9	4:3 support 16:9	4:3 support 16:9	4:3 support 16:9	4:3 support 16:9	4:3 support 16:9	4:3 support 16:9	4:3 support 16:9
Keystone Correct	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Digital Zoom	2x	2x	2x	2x	2x	2x	2x	2x	2x	2x	2x	2x
Projection Options	Front, rear, table	Front, rear, table	Front, ceiling, rear, table	Front, ceiling, rear, table	Front, ceiling, rear, table	Front, ceiling, rear, table	Front, ceiling, rear, table	Front, ceiling, rear, table	Front, ceiling, rear, table	Front, ceiling, rear, table	Front, ceiling, rear, table	Front, ceiling, rear, table
Projection Distance	3.9ft - 41.9ft	3.9ft - 38.7ft	3.9ft - 38ft	3.9ft - 38.7ft	3.9ft - 34.7ft	3.9ft - 36.4ft	3.9ft - 36.5.2ft	3.9ft - 37.7ft	3.9ft - 26.2ft	3.9ft - 37.7.2ft	3.9ft - 37.7.2ft	3.9ft - 37.7.2ft
Image Size	28"-300" Diagonal	26" - 300" Diagonal	26" - 300" Diagonal	26" - 300" Diagonal	34"-300" Diagonal	28"-300" Diagonal	28"-300" Diagonal	27"-300" Diagonal	38"-300" Diagonal	27"-300" Diagonal	27"-300" Diagonal	27"-300" Diagonal
Video Signals	NTSC, PAL, YCbCr, YPbPr (480p, 720p, 1080i)	NTSC, PAL, YCbCr, YPbPr (480p, 720p, 1080i)	NTSC, PAL, YCbCr, YPbPr (480p, 720p, 1080i)	NTSC, PAL, YCbCr, YPbPr (480p, 720p, 1080i)	NTSC, PAL, YCbCr, YPbPr (480p, 720p, 1080i) Built-in Line Doubler	NTSC, PAL, YCbCr, YPbPr (480p, 720p, 1080i) Built-in Line Doubler	NTSC, PAL, YCbCr, YPbPr (480p, 720p, 1080i) Built-in Line Doubler	NTSC, PAL, YCbCr, YPbPr (480p, 576p, 720p, 1080i) Built-in Line Doubler	NTSC, PAL, YCbCr, YPbPr (480p, 576p, 720p, 1080i) Built-in Line Doubler	NTSC, PAL, YCbCr, YPbPr (480p, 576p, 720p, 1080i) Built-in Line Doubler	NTSC, PAL, YCbCr, YPbPr (480p, 576p, 720p, 1080i) Built-in Line Doubler	NTSC, PAL, YCbCr, YPbPr (480p, 576p, 720p, 1080i) Built-in Line Doubler
Built-in Speaker	Mono 0.5 watt	Mono 0.5 watt	Mono 0.5 watt	Mono 0.5 watt	Mono 0.8 watt	Mono 0.8 watt	Mono 0.8 watt	Mono 0.8 watt	Mono 0.8 watt	Mono 0.8 watt	Mono 0.8 watt	Mono 0.8 watt
Dimensions (Inches)	8.2L x 6.2W x 1.38H	6.9L x 7.3W x 1.8H	9.5L x 7.5W x 2.1H	9.5L x 7.5W x 2.1H	9.7L x 8.5W x 2.3H	9.7L x 8.5W x 2.3H	9.4L x 8.5W x 2.4H	9.9L x 8.5W x 2.4H	10.2L x 8.5W x 2.4H	12.6L x 10.1W x 3.3H	12.6L x 10.1W x 3.3H	12.6L x 10.1W x 3.3H
Security Features	Password & Keylock	Keylock	Keylock	Keylock	Password & Keylock	Password & Keylock	Password & Keylock	Password & Keylock	Password & Keylock	Password & Keylock	Password & Keylock	Password & Keylock
Eco-Mode	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Special Features	Only 1.38" Thin!!!	Brightest 2 lb, Unplug & Go, Iris Lens Cover	Aggressive XGA Pricing	Brightest 3lb Projector, Wireless, CF Memory	Aggressive Entry Level Pricing	Aggressive Entry Level Pricing	RGB Output RS-232 Control	RS-232 Control	Bright Mode (Up to 3000 Lumens) RS-232 Control	RS-232 Control	RS-232 Control	USB/CF Card Slots, RS-232 Control, Wireless Networking

PLUS

PLUS Vision Corp. 9610 SW Sunshine Ct, Suite 800 Beaverton, OR 97005
Toll Free: 866-427-8855 Phone: 503-748-8700 fax: 503-748-8767 web: <http://www.plus-america.com>